

Technical Data Sheet

GRAFFITI STRIPPER™

Restoration Cleaner

Product Data and Application Method

PRODUCT NAME

GRAFFITI STRIPPER™
Multi-surface graffiti remover

MANUFACTURER

Chemical Products Industries, Inc
7649 SW 34th St., Oklahoma City, Ok 73179
(800)624-4356 (405) 745-2070

PRODUCT DESCRIPTION

Non-flammable, non-toxic, easy to use water-based graffiti remover. The low-volatility nature of Graffiti Stripper maintains a very slow evaporation rate, allowing it to remain on the surface to work and soften coatings. Depending on the nature of the coating to be removed, it will soften or wrinkle, usually within 20-30 minutes.

CHARACTERISTICS

Clear thixotropic gel with a mildly sweet odor.

USAGE

Safe to use on glass, masonry, metal, plaster, fiberglass and wood.

BENEFITS

- Effective on many materials
- Gel consistency reduces waste
- Can be used indoors
- Softens coatings
- No-fumes or caustics
- Water-soluble
- Biodegradable

TECHNICAL DATA

Color	Slightly Amber
Odor	Sweet - Amine
pH	10-11
Specific Gravity	1.0
Flash point	None
Solubility in Water	100%
VOC	400 g/l

COVERAGE RATES

Always test. Coverage rates will vary depending on level of contamination.

Follow recommended coverage rate guidelines, however, never exceed application past the point of rejection, i.e. puddling.

Architectural Block:
75-150 sq. ft.

Concrete:
75-200 sq. ft.

Natural Stone:
100-250 sq. ft.

Coverage rates depend on surface texture and porosity.

PREPARATION

Graffiti Stripper should be applied when surface and air temperatures are 40° F (4° C) or above. If freezing has occurred, allow the masonry to thaw completely before application.

ALWAYS TEST

In an inconspicuous area to determine the suitability of this product for the intended use.

APPLICATION

Always test each type of surface, paint coating and graffiti stain for suitability and results before the overall application. Let tests dry thoroughly before inspection.

Apply liberally to the graffiti tag using a brush or airless spray equipment. Apply a uniform coat.

www.chemicalproductsokc.com

(Continued)

Let dwell on the surface for 10-20 minutes, depending on the type and severity of the graffiti tag and type of surface.

Periodic agitation with a stiff bristle brush improves product penetration through graffiti and/or sacrificial graffiti coating. Remove the gel and as much of the graffiti residue as possible from the surface.

Thoroughly pressure-water rinse at 400-600 psi. Hot water is preferred if available.

Let the surface dry completely before applying a new anti-graffiti coating. Ensure all product has been rinsed away.

LIMITATIONS

Do not dilute or alter.

For best results apply to the surface between 80° and 100° F. The colder the conditions the slower Graffiti Stripper works.

Note: Not all coatings such as, cross linked epoxies and urethanes, can be removed with this product.

PRECAUTIONS

For specific information regarding safe handling of this material refer to the Material Safety Data Sheet.

AVAILABILITY

Graffiti Stripper is available in 1, 5 and 55 gallon drums throughout the United States. Contact Chemical Products Industries, Inc. at 800-624-4356 or 405-745-2070 for a sales representative in your area.

TECHNICAL SERVICE

Technical service engineers and chemists are available to answer questions on product performance, application methods and chemical composition.

LIMITED WARRANTY

Chemical Products Industries, Inc. warrants this product to be free from defects. Chemical Products Industries, Inc. shall not be held responsible in any manner for any personal injury or property damage or other type of loss resulting from, or related to, the handling, storage, or use of this material. Since Chemical Products Industries, Inc. shall have no control of the use of this product described herein; Chemical Products Industries, Inc. assumes no liability for loss or damage incurred from the improper use of such product.