



### PRODUCT NAME

CP-Graffiti & Water Repellent

### MANUFACTURER

Chemical Products Industries, Inc.  
7649 SW 34<sup>th</sup> St., Oklahoma City, Ok 73179  
(800) 624-4356 (405) 745-2070

### PRODUCT DESCRIPTION

Mixture of silane/siloxane compounds. Emulsion based on a silicone and organic wax that is used as a self-priming, sacrificial coating.

### APPLICATIONS

Designed for protecting absorbent mineral substrates, e.g. concrete, masonry, brick, natural and artificial stones, and plaster against graffiti damage.

### BENEFITS

- One-part system
- Effective on many surfaces
- Will acquire a slight wax appearance
- Oil resistant
- Weather resistant
- Good water repellency
- Water-vapor permeable
- Water-based
- Environmentally compatible.

### GRAFFITI REMOVAL

Use hot water or steam cleaning, preferably with high-pressure equipment (e.g. 90 C, 800-1000 psi) or chemical clean with Chemical Products' safe and effective Graffiti Stripper.

The sacrificial portion of this coating will withstand 1-3 washings before recoating is necessary. Note: Chemical Products recommends Graffiti Stripper

### LIMITATIONS

Not intended for below-grade waterproofing. Should not be applied if the surface temperature is below 20° F or above 100° F,

if rain is expected within two hours following application, or if high winds or other conditions prevent proper application. If rain has preceded the application, the surface should be allowed to dry at least 24 hours. CP-Graffiti & Water Repellent will leave a residue on non-porous substrates such as glass windows, metal frames and painted surfaces. Caution should be taken with specialty coated glass or plastic windows. Check compatibility before application.

### PRECAUTIONS

For specific information regarding safe handling of this material refer to the Material Safety Data Sheet.

### INSTALLATION

Perform a test area on the required surface(s) to determine product effectiveness and coverage rates. A coverage rate of 125 square feet per gallon is recommended for most masonry surfaces.

Can be applied by spraying, brushing or rolling. For best results two applications are recommended with the second application applied using a wet on wet technique, i.e., the surface is wet from the first application but not glossy. During application, precautions should be taken to protect the surrounding area from overspray and run off of CP-Graffiti & Water Repellent.

Best results are obtained by applying CP-Graffiti & Water Repellent on dry porous substrates. As a standard procedure, fresh concrete should be allowed to dry for 28 days before applying.

In addition, the actual amount of material that is used for each application is dependent on the absorptive capacity of the substrate.

prior to high-pressure cleaning for best results.

### AVAILABILITY

CP-Graffiti & Water Repellent is available in 1, 5 and 55 gallon containers to approved applicators throughout the United States. Contact Chemical Products Industries, Inc. at 800-624-4356 for a sales representative in your area.

### TECHNICAL SERVICE

Technical service engineers and chemists are available to answer questions on product performance, application methods and chemical composition.